

TG-LD15150W

LED Linear High Bay

5FT 150W



The Line D LED Linear High Bay offers 4 different optical patterns, which enable you to handle the most demanding indoor universal lighting situations. With a modular design, this stylish luminaire provides improved illumination performance while reducing energy consumption.


Benefits:

- Reliable light output throughout lifetime
- Powerful energy and maintenance savings
- Attractive return on investment(ROI) with superior performance

Features:

- DLC V4.4 qualified
- Low glare rating and CRI of more than 70
- Modular design, built-in power supply design
- Available in 2-, 3-, 4- and 5-foot lengths
- 0-10V Dimmable
- Wide variety of optics
- UL damp listed, designed for easy cleaning
- 5 years warranty

Dimensions:



Length: 1500 mm
Width: 140 mm
Height: 110 mm

Line D LED Linear High Bay

Electrical Specifications:

Model No.	TG-LD15150W
Wattage	150 W
LED Source	3030 SMD
Number of LEDs	165
Number of Optics	5
Driver Brand	INVENTRONICS™
Driver Model	EUG-150S210DT
Input Voltage	100-277V AC 50/60Hz
Working Temperature	-30 to +45°C
Power Factor(PF)	>0.95
Driver Efficiency	92.5%

Photometric Specifications:

Lumen Output	17,250 lm
Lumen Efficacy	115 lm/W
CRI	>70
Beam Angles	30° , 60° , 90° , Double Asymmetric
Optional Dimmable	0-10V
Color Temperature(CCT)	4000K 5000K

Mechanical Specifications:

IP Rating	IP54
Lifespan(L70)	≥50,000 hours
Housing	6063 aluminum alloy with anti-corrosion coating
Optic	PMMA
Mounting	Cable-suspended mount/ Direct mount(fixation by bracket, angle can be adjusted)
Cabling	0.3m long PVC(extended available)
Fixture Dimension	1500 × 140 × 110 mm
Fixture Weight	8.0 kg
Lifetime Testing	To LM-79
Warranty	5 Years

Line D LED Linear High Bay

Certifications:

CE&RoHS Compliant
DLC - Qualified Product(DLC V4.4)
Certified to ANS/UL STD. 1598 UL STD. 8750
Certified to CSA STD. C22.2 No. 250.0

Package:

Environmentally friendly packaging materials (EPE)
EPE foam inner package + outer carton
Carton size: 155 × 19 × 17 cm
Quantity/carton: 1
Gross weight/carton: 10 kg
Cable-suspended accessories: included

Applications:

- Interior high-bay, auto dealership, municipal, retail & grocery, industrial, food production and warehouse, indoor sports halls, exhibition halls



IES files for this fixture are available by request